

All previously approved batteries keep their approval for their natural life cycle

**EUROPEAN FEDERATION RADIO-CONTROLLED AUTOMOBILES**

Manufacturer	TYPE / Range	Picture as illustration only	Alternate presentation	EFRA Specification, new unused cell	remark	Approval date
Intellect	SC-3600			Revised diam 2006 Diam 23,0 +0/-1,0mm H: 43,0 +0/ -1,5mm W: 65 +/- 2g		31/12/2005
Intellect	SC-3800			High-drain type Diam 23,0 +0/-1,0mm H: 43,0 +0/ -1,5mm W: 66 +/- 2g		31/12/2005
Intellect	SC-4200			High-drain type Diam 23,0 +0/-1,0mm H: 43,0 +0/ -1,5mm W: 66 +/- 2g		31/12/2005
Intellect	YOKOMO SC-3800			X3800IB - Zap2 Diam 23,0 +0/-1,0mm H: 43,0 +0/ -1,5mm W: 64 +/- 2g		31/12/2005
Intellect	YOKOMO SC-4200			X4200IB - Zap2 Diam 23,0 +0/-1,0mm H: 43,0 +0/ -1,5mm W: 66 +/- 2g		31/12/2005
VTEC	SC-3700UP			Revised diam 2006 Ultra performance Diam 23,0 +0/-1,0mm H: 43,0 +0/ -1,5mm W: 64 +/- 2g		31/12/2005
VTEC	SC-3800UP			3800 Fat Boy Diam 23,0 +0/-1,0mm H: 43,4 +0/ -1,5mm W: 65 +/- 2g		31/12/2005
VTEC	SC-4200UP			4200 Big Mama Diam 23,0 +0/-1,0mm H: 43,0 +0/ -1,5mm W: 66 +/- 2g		31/12/2005
Yunton	SC-4000			Batt 4000 Diam 23,0 +0/-1,0mm H: 43,0 +0/ -1,5mm W: 66 +/- 2g		31/12/2005
? Made in China	INFINITE POWER IP3800SC			IP3800SC Diam 23,0 +0/-1,0mm H: 43,3 +0/ -1,5mm W: 68,5 +/- 2g		31/12/2005
Shenzhen	GP430SCHR			Gold Peak 4300 Diam 23,0 +0/-1,0mm H: 43,3 +0/ -1,5mm W: 66 +/- 2g	(Typical 4100Mah) Cherry/Green for GP430SCHR Yellow/Green for GP430SCHC	31/12/2005

All cells measured with same tool and electronic scale. All dimensions taken at ambient temperature. All data valid only for new unused cells. Fast charging may result in cell distortion, laboratory simulations show that cells do not expand more than 0,3mm, All previously approved cells keep their approval for their natural lifecycle