



APPROVED BATTERY LIST, Jan. 2007.

EUROPEAN FEDERATION RADIO CONTROLLED AUTOMOBILES.

All previously approved batteries keep their approval for their natural life cycle

All Cells when submitted for approval, to have maximum dimensions of :- Dia. 23.00 mm, Ht. 43.00 mm.

Manufacturer	Type / Range	Illustration only	Alternative view.	Manufacturer Data.	EFRA measured Specification,	Approval Date
Intellect	SC-3600			New specification 2006. Dia. 23,0 +0/-1,0 mm. Ht. 43,0 +0/ -0,5 mm. Wt. 61/65 gm.	Range Efra sample specs: Wt. 63,1/63,9 gm.	31/12/2005
Intellect	SC-3800			High-drain type Dia. 23,0 +0/-0,5 mm. Ht. 43,0 +0/ -0,5mm. Wt. 64/68 gm.	Range Efra sample specs: Wt. 65,1/66,8 gm.	31/12/2005
Intellect	SC-4200			High-drain type Dia. 23,0 +0/-0,5 mm. Ht. 43,0 +0/ -0,5mm. Wt. 65/69 gm.	Range Efra sample specs: Wt. 66,6/67,9 gm.	31/12/2005
Intellect	YOKOMO SC-3800			X3800IB - Zap2 Dia. 23,0 +0/-0,5 mm Ht. 43,0 +0/ -0,5 mm Wt. 64/68 gm.		31/12/2005
Intellect	YOKOMO SC-4200			X4200IB - Zap2 Dia. 23,0 +0/-0,5 mm Ht. 43,0 +0/ -0,5 mm Wt. 65/69 gm.		31/12/2005
VTEC	SC-3700UP			New specification 2006 Dia. 23,0 +0/-1,0 mm Ht. 43,0 +0/ -1,0 mm Wt. 62.5/66.5 gm.	Range Efra sample specs: Wt. 64,7/65,5 gm.	31/12/2005
VTEC	SC-3800UP			3800 Fat Boy Dia. 23,0 +0/-1,0 mm Ht. 43,0 +0/-1,0 mm Wt. 64/68 gm.	Range Efra sample specs: Wt. 66,4/66,7 gm.	31/12/2005
VTEC	SC-4200UP			4200 Big Mama Dia. 23,0 +0/-1,0 mm Ht. 43,0 +0/-1,0 mm Wt. 65/69 gm.	Range Efra sample specs: Wt. 67,1 gm.	31/12/2005
Yungton	SC-4000			Batt 4000 Dia. 23,0 +0/-1,0 mm Ht. 43,0 +0/-1,0 mm Wt. 64/68 gm.		31/12/2005
? Made in China	INFINITE POWER IP3800SC			IP3800SC Dia. 23,0 +0/-1,0 mm Ht. 43,0 +0/-1,0 mm Wt. 66,5/70,5 gm.		31/12/2005
GP	GP430SCHR & GP430SCHC			Gold Peak 4300 Dia. 23,0 +0/-1,0 mm Ht. 43,0 +0/-1,0 mm Wt. 66,0 gm. No tolerance	Range Efra sample specs: Wt. 66,3/66,6 gm.	31/12/2005

(EP) East Power	SC-4200			East Power 4200. NiMH Red Disc at positive end. Dia. 23,0 +0/-1,0 mm Ht. 43,0 +0/-0,5 mm Wt. 68/72 grm.	Range Efra sample specs: Dia. 22,88/22,95 mm. Ht. 42,83/42,98 mm Wt. 70,6/71,4 grm.	30/09/2006
GP	GP430SCHR & GP430SCHC			Gold Peak 4300. NiMH. Revised spec. 2007 May have H-MPV sticker. Man. Data - 66/70 grm.	Range Efra sample specs: Dia. 22,95/23,00 mm. Ht. 42,78/42,95 mm Wt. 68,6/69,0 grm.	31/12/2006
GP	GP460SCHR			Gold Peak 4600. NiMH. Man. Data - 68/72 grm.	Range Efra sample specs: Dia. 22,94/23,00 mm. Ht. 42,90/43,00 mm Wt. 69,2/69,5 grm.	31/12/2006
VTEC	SC-4200UP			VTEC 4200. NiMH. 'Big Mama' Revised spec. 2007. Man. Data - 67/73 grm.	Range Efra sample specs: Dia. 22,90/22,98 mm. Ht. 42,71/42,88 mm Wt. 70,4/70,8 grm.	31/12/2006
Vapex	VP4300SCUP			Vapex 4300. NiMH. Man. Data - 67/73 grm.	Range Efra sample specs: Dia. 22,90/22,93 mm. Ht. 42,68/42,79 mm Wt. 70,3/71,5 grm.	31/12/2006
(EP) Enrich power	SC-3800			Enrichpower 3800. NiMH. Black Disc at positive end. Man. Data - 66/67 grm.	Range Efra sample specs: Dia. 22,91/22,95 mm. Ht. 42,96/43,00 mm Wt. 66,6/67,0 grm.	31/12/2006
Grepow	UP43SC4200P HV			Grepow 4200. NiMH. 'Hi Volt Plus' Man. Data - 68/74 grm.	Range Efra sample specs: Dia. 22,96/23,00 mm. Ht. 42,65/42,91 mm Wt. 68,8/70,8 grm.	31/12/2006
Grepow	UP43SC4500P			Grepow 4500. NiMH. Man. Data - 67/73 grm.	Range Efra sample specs: Dia. 22,91/23,00 mm. Ht. 42,60/42,88 mm Wt. 68,3/68,9 grm.	31/12/2006
Intellect	SC-4200			Intellect 4200. NiMH. Revised spec. 2007. May have SHV or WC sticker. Man. Data - 67/73 grm.	Range Efra sample specs: Dia. 22,94/23,00 mm. Ht. 42,67/42,88 mm Wt. 70,6/71,1 grm.	31/12/2006
Intellect	Check Point SC-4200			Check Point 4200. NiMH. Man. Data - 67/73 grm.	Range Efra sample specs: Dia. 22,93/23,00 mm. Ht. 42,70/42,90 mm Wt. 70,6/71,4 grm.	31/12/2006
Intellect	EPIC EP4200IB			EPIC 4200. NiMH. Man. Data - 67/73 grm.	Range Efra sample specs: Dia. 22,90/22,96 mm. Ht. 42,73/42,88 mm Wt. 70,5/71,3 grm.	31/12/2006
Intellect	Yokomo X4200 IB			Yokomo 4200. NiMH. Revised spec. 2007. Man. Data - 67/73 grm.	Range Efra sample specs: Dia. 22,91/23,00 mm. Ht. 42,75/42,88 mm Wt. 70,5/71,2 grm.	31/12/2006